

InstaTile

Recycled Rubber Gym Tiles

TECHNICAL SPECIFICATION

High Performance, Environmentally Friendly, Rubber Crumb Gym Tiles

Commercial, professional and home gyms

Guaranteed for 5 years (Manufacturers limited warranty)

InstaTile Specification			
Product Reference	GT15	GT20	GT40
Thickness	15mm	20mm	40mm
Colour (Full Pigmented)	Black Tiles with coloured flecks are available on request		
Dimensions	500mm x 1000mm		
	1000mm x 1000mm		
Manufacturing Tolerances	Width / Length +/- 2mm – Thickness +/- 1mm		
Profile	Bevel Edge		
Density	940 kg/m ³		
Nominal Weight (500mm x 1000mm)	7.05 kg/m ²	9.4 kg/m ²	18.8 kg/m ²
Nominal Weight (1000mm x 1000mm)	14.1 kg/m ²	18.8 kg/m ²	37.6 kg/m ²
Material	SBR Granules / Recycled Tyre Rubber		
Bonding Agent	Polyurethane		
Hardness	65 Shore A - Tolerance +/- 8		
Installation Process	Bond to sub floor with F Ball F74 (2mm x 6mm trowel) or Mapei VS90 PLUS adhesive or other equivalent adhesives suitable for rubber flooring		

Guarantee covers manufacturing defects but does not include wear and tear. This guarantee is subject to the InstaCoustic Ltd standard terms and conditions.

InstaTile Technical Specification	Version: 03	Version Date: August 2019	Page 1 of 1
-----------------------------------	-------------	---------------------------	-------------