

InstaLay 65 (Plain Product)

TECHNICAL SPECIFICATION

High Performance, Environmentally Friendly, Rubber Crumb Underlays

Suitable for stretch-fit, single-stick, double-stick installation methods and also under-screed applications

Rating: HC/U – Heavy Contract Use, suitable for heavy foot and wheel traffic and castor chairs

Manufactured using recycled rubber crumb

Guaranteed for 10 Years

Roll Size: 1.372m x 10.92m (15.0m² / roll)

<u>Specification</u>	<u>BS Requirements</u>	<u>Result</u>	<u>Test Method</u>
Nominal Weight Density Nominal Roll Weight		2.2 kg/m ² 370 kg/m ³ 33 kg	
Colour and Appearance Compound Bonding Agent		Black rubber crumb on a fibreglass backing. Recycled tyre tread (minimum 80%) Synthetic Laytex	
Breaking Strength and Elongation Breaking Strength – Direction 1 Breaking Strength - Direction 2 Elongation – Direction 1 Elongation – Direction 2 Elongation at Break – Direction 1 Elongation at Break – Direction 2	Minimum 40N 10% Maximum extension for applied force of 40N	240.3N 328.2N 1.093% 1.907% 3.248% 5.250%	BS 5808 BS 5808 BS 5808
Loss in Thickness a) Static loading: recovery period 24hrs b) Dynamic loading: after 1000 impacts	Maximum 15% Maximum 15%	1.6% 3.2%	BS 4939 BS 4052
Nominal Thickness Thickness Deviation a) Mean original thickness from the nominal thickness b) Difference between maximum and minimum original thickness	Maximum 12% Maximum 3mm	6.0mm 0.02% 0.4mm	BS 4051 BS 4051
Compression after Dynamic Loading	Minimum 2mm, Maximum 7mm	2.2mm	BS 4098

Product Codes: IL65	Version: 08	Version Date: January 28, 2020	Page 1 of 2
---------------------	-------------	--------------------------------	-------------

InstaFloor UK

Tel: +44 (0)118 973 9560

Email: sales@instafloor.co.uk

Web: www.instafloor.co.uk

InstaLay 65 (Plain Product)

TECHNICAL SPECIFICATION

High Performance, Environmentally Friendly, Rubber Crumb Underlays

Suitable for stretch-fit, single-stick, double-stick installation methods and also under-screed applications

Rating: HC/U – Heavy Contract Use, suitable for heavy foot and wheel traffic and castor chairs

Manufactured using recycled rubber crumb

Guaranteed for 10 Years

Roll Size: 1.372m x 10.92m (15.0m² / roll)

<u>Specification</u>	<u>BS Requirements</u>	<u>Result</u>	<u>Test Method</u>
Work of Compression after Dynamic Loading	Minimum 50J/m ² , Maximum 200J/m ²	73J/m ²	BS 4098
Retention of Original Work of Compression	Minimum 40%	102.8%	BS 4098
Resistance to Breaking or Cracking	No cracks longer than 50mm	No cracks visible	BS 5808
Odour		No objectionable odour	
Thermal Resistance (R)		1.01 Togs	BS 4745
Acoustic Performance			
Measured Improvement of Impact Sound (ΔL_w)		25dB ΔL_w	BS EN ISO 140-8: 1998 & BS EN ISO 717-2: 1997
Reaction to Fire		Class E _{fl}	BS EN ISO 11925-2:2002

Please Note:

- InstaLay Self-Adhesive products must not be installed at temperatures below 10°C.
- For further information on the guarantee and product warranty, please refer to the InstaLay guarantee document which is available from the www.instafloor.co.uk website.

Product Codes: IL65	Version: 08	Version Date: January 28, 2020	Page 2 of 2
---------------------	-------------	--------------------------------	-------------