

EZY-INSTALL - DUAL BOND

High Performance, Environmentally Friendly, Magnetically Receptive Acoustic Rubber Underlay

Domestic and commercial use

Manufactured using recycled rubber crumb and metallised resin coating

Roll Size: 2.5mm - 1.0m x 5.0m (5.0m² / roll) / 3ft 3" x 16ft 5" (53.8ft² / roll)

Specification	BS Requirements	Result	Test Method
Nominal Weight		2 kg/m ² / 0.4 lb/ft ²	
Nominal Roll Weight		10 kg / 22 lb	
Colour and Appearance		Black rubber crumb on a non-woven polypropylene backing	
Compound		Recycled tyre tread (minimum 80%)	
Bonding Agent		Synthetic Latex	
Magnetic Receptive Coating		Metallised resin coating with dry adhesive tack	
Loss in Thickness			
a) Static loading: recovery period 1hr		4.20%	BS EN 14499:2015
b) Static loading: recovery period 24hrs	Maximum 15%	3.60%	BS EN 14499:2015
c) Dynamic loading: after 1000 impacts	Maximum 15%	8.0%	BS EN 14499:2015
Nominal Thickness		2.5mm	
Thickness Deviation			
a) Mean original thickness from the nominal thickness	Maximum 12%	0.00%	
b) Difference between maximum and minimum original thickness	Maximum 3mm	0.3mm	
Compression after Dynamic Loading		0.5mm	BS EN 14499:2015
Work of Compression after Dynamic Loading		19J/m ²	BS EN 14499:2015
Retention of Original Work of Compression			BS EN 14499:2015

EZY-INSTALL - DUAL BOND

High Performance, Environmentally Friendly, Magnetically Receptive Acoustic Rubber Underlay

Specification	BS Requirements	Result	Test Method
Resistance to Breaking or Cracking	No cracks longer than 50mm	No cracks visible	BS EN 14499:2015
Odour		No objectionable odour	
Permeability to Water Vapour			
Water Vapour Transmission Rate (WVTR) / g/m ² .day		0.09 / g/m ² .day	EN ISO 15106
Vapour Resistance / MNs/g		2887 / MNs/g	EN ISO 15106
Acoustic Performance			
Measured Improvement of Impact Sound (ΔL_w)		17dB ΔL_w *	BS EN ISO 10140-3: 2010 & BS EN ISO 717-2: 2013
Impact Insulation Class (IIC)		IIC 50 **	ASTM – E492-09, E989-06 & E2179-03

Please Note:

- For further information on the guarantee and product warranty, please refer to the Ezy-Install guarantee document which is available on request.
- * Tested on 160mm / 6" concrete floor with no floor covering or ceiling system.
- ** Ezy-Install with LVT (2.5mm) tested on 160mm / 6" concrete floor with no drop ceiling.

MANUFACTURER:

InstaFloor t/a InstaCoustic Ltd, Insta House, Ivanhoe Road, Hogwood Business Park, Wokingham, Berkshire, RG40 4PZ

Tel: 01189 739560

Email: sales@instafloor.co.uk

Web: www.instafloor.co.uk