

M50 RUBBER/ PLASTICS/ CORK / LINO / CARPET TILING / SHEETING

110 - Resilient Floor Tiling InstaFloor/Innov8Floors LINO DL

110 RESILIENT FLOOR TILING

LOCATION

Heavy use areas - Office, Retail, Hospitality, Educational and Residential areas.

BASE

Refer to InstaFloor/Innov8Floors installation instructions.

PREPARATION:

Sub-floors should be prepared in accordance with BS 5325, BS 8203, BS 8204, BS 8201 and BS 8425 or other relevant Standards.

FABRICATED UNDERLAY:

InstaLay 25hg underlay loose laid to sub floor creating floating floor.

PRODUCT REFERENCE:

LINO DL (Dry-Back)

- Thickness: 4mm
- Backing Type: Cork Composite
- Weight (kg/m²): 4
- Tile Size: 390mm x 620mm / 200mm x 1235mm
- Dimensional Stability EN434: < 0.05%
- Thermal Resistance EN 12524 (m² K/W): 0.06
- Impact Sound Δ Lw: 16dB
- Classification EN16511: Domestic 23 / Commercial 33
- Reaction of fire EN ISO 9239-1: Cfl s1 (B1)
- Coefficient of friction EN51130: R10

MANUFACTURER:

InstaFloor t/a InstaCoustic Ltd, Insta House, Ivanhoe Road,
Hogwood Business Park, Wokingham, Berkshire, RG40 4PZ

Tel: 0118 973 9560

Email: sales@instafloor.co.uk

Web: www.instafloor.co.uk

M50 RUBBER/ PLASTICS/ CORK / LINO / CARPET TILING / SHEETING

110 - Resilient Floor Tiling InstaFloor/Innov8Floors LINO DL

GENERALLY

210 WORKMANSHIP:

- All bases must be rigid, dry, sound, smooth and free from grease, dirt and other contaminants before coverings are applied.
- Installation should be carried out in strict accordance with the InstaFloor/Innov8Floors installation instructions

320 STORAGE:

Store materials in a clean, warm, dry, well ventilated location. Keep in original packing until conditioning commences.

330 COMMENCEMENT:

Do not lay materials until building is weathertight, wet trades have finished their work, the building is well dried out, all paintwork is finished and dry.

340 CONDITIONING:

Before laying commences thoroughly condition materials by unpacking and separating in the spaces where they are to be laid. Minimum conditioning time and temperature to be as recommended by InstaFloor/Innov8Floors. Extend period by a factor of 2 for materials stored or transported at a temperature of less than 10°C immediately prior to laying.

350 ENVIRONMENT:

Before, during and after laying, provide adequate ventilation and maintain temperature and humidity approximately at levels which will prevail after the building is occupied.

360 UNDERFLOOR HEATING:

Strictly follow the InstaFloor/Innov8Floors underfloor heating installation instructions for the type of resilient floor covering being installed.