

M40 – STONE / CONCRETE / QUARRY / CERAMIC TILE / MOSAIC

115 – Natural Stone InstaFloor/Innov8Floors V STONE

110 RESILIENT FLOOR TILING

LOCATION

Heavy use areas - Office, Retail, Hospitality, Educational and Residential areas.

BASE

Refer to InstaFloor/Innov8Floors installation instructions.

PREPARATION:

Sub-floors should be prepared in accordance with BS 5325, BS 8203, BS 8204, BS 8201 and BS 8425 or other relevant Standards.

FABRICATED UNDERLAY:

InstaLay 25hg underlay loose laid to sub floor creating floating floor.

PRODUCT REFERENCE:

V STONE Real Stone/ Real Slate (Dry-Back)

- Thickness mm: 4mm / 6mm
- Backing Type: Cork Composite
- Weight EN 430 (kg/m²): 4 / 6
- Tile Size: 305mm x 1235mm
- Dimensional Stability EN434: < 0.05%
- Thermal Resistance EN 12524 (m² K/W): 0.08
- Impact Sound Δ Lw: 16dB
- Classification EN16511: Domestic 23 / Commercial 31
- Reaction of fire EN ISO 9239-1: Dfl s1
- Coefficient of friction EN51130: R11

MANUFACTURER:

InstaFloor t/a InstaCoustic Ltd, Insta House, Ivanhoe Road,
Hogwood Business Park, Wokingham, Berkshire, RG40 4PZ

Tel: 0118 973 9560

Email: sales@instafloor.co.uk

Web: www.instafloor.co.uk

M40 – STONE / CONCRETE / QUARRY / CERAMIC TILE / MOSAIC

115 – Natural Stone InstaFloor/Innov8Floors V STONE

GENERALLY

210 WORKMANSHIP:

- All bases must be rigid, dry, sound, smooth and free from grease, dirt and other contaminants before coverings are applied.
- Installation should be carried out in strict accordance with the InstaFloor/Innov8Floors installation instructions

320 STORAGE:

Store materials in a clean, warm, dry, well ventilated location. Keep in original packing until conditioning commences.

330 COMMENCEMENT:

Do not lay materials until building is weathertight, wet trades have finished their work, the building is well dried out, all paintwork is finished and dry.

340 CONDITIONING:

Before laying commences thoroughly condition materials by unpacking and separating in the spaces where they are to be laid. Minimum conditioning time and temperature to be as recommended by InstaFloor/Innov8Floors. Extend period by a factor of 2 for materials stored or transported at a temperature of less than 10°C immediately prior to laying.

350 ENVIRONMENT:

Before, during and after laying, provide adequate ventilation and maintain temperature and humidity approximately at levels which will prevail after the building is occupied.

360 UNDERFLOOR HEATING:

Strictly follow the InstaFloor/Innov8Floors underfloor heating installation instructions for the type of resilient floor covering being installed.